



Accessories Injection Technique

MSH Sleeve



MSH-Ø	mm	9	13	18	
MSH-Length	mm	50	85	130	85
Drill-Ø	mm	12	16	20	
Drill depth	mm	55	90	140	90
Filling volume	ml	4	12	18	23
For thread	M	≤ 8	≤ 12	≤ 12	≤ 16
		1710141	1710142	1710143	1710144

MSM Metal Sleeve



MSH-Ø	mm	11	15	20
MSH-Length	mm	1000	1000	1000
Drill-Ø	mm	12	16	22
Filling volume	ml/mm	0.1	0.2	0.35
For thread	M	≤ 8	≤ 12	≤ 16
		1710151	1710152	1710153

MIT-S Anchor Rod galvanised



Threaded rod steel quality 5.8
Nut strength category I8I
Washer DIN 125

Rod-Ø	M	6	8	10	12	
Spanner size	mm	10	13	17	19	
Rod length	mm	70	100	110	115	
Drill-Ø Concrete	mm	8	10	12	14	
Drill-Ø perforated brick with MSH	mm	12	12	16	16	16
Usable length	mm	15	40	10	15	20
		1710051	1710052	1710053	1710054	

MIGH Anchor Sleeve with internal thread



Internal thread	M	6	8	10	12
MIGH-Ø	mm	8	12	14	16
MIGH-Length	mm	45	80	80	80
Drill-Ø Concrete	mm	10	14	16	18
		1710060	1710061	1710062	1710063

MIT-ZK Centre Cone



Centering and Fixation

for thread	M	8	10	12	16	20
		1710070	1710071	1710072	1710073	1710074